OQL

Motivation:

- Relational languages suffer from *impedance mismatch* when we try to connect them to conventional languages like C or C++.
  - ❖ The data models of C and SQL are radically different, e.g. C does not have relations, sets, or bags as primitive types; C is tuple-at-a-time, SQL is relation-at-a-time.
- OQL is an attempt by the OO community to extend languages like C++ with SQL-like, relation-at-a-time dictions.

OQL Types

- Basic types: strings, ints, reals, etc., plus class names.
- Type constructors:
  - `Struct` for structures.
  - Collection types: set, bag, list, array.
- Like ODL, but no limit on the number of times we can apply a type constructor.
- Set(Struct()) and Bag(Struct()) play special roles akin to relations.

OQL Uses ODL as its Schema-Definition Portion

- For every class we can declare an *extent* = name for the current set of objects of the class.
  - Remember to refer to the extent, not the class name, in queries.

```
interface Bar
    (extent Bars)
{
    attribute string name;
    attribute string addr;
    relationship Set<Sell> beersSold
        inverse Sell::bar;
}

interface Beer
    (extent Beers)
{
    attribute string name;
    attribute string manf;
    relationship Set<Sell> soldBy
        inverse Sell::beer;
}

interface Sell
    (extent Sells)
{
    attribute float price;
    relationship Bar bar
        inverse Bar::beersSold;
    relationship Beer beer
        inverse Beer::soldBy;
}
```

Path Expressions

Let x be an object of class C.

- If a is an attribute of C, then $x.a$ = the value of a in the x object.
- If r is a relationship of C, then $x.r$ = the value to which x is connected by r.
  - ❖ Could be an object or a collection of objects, depending on the type of r.
- If m is a method of C, then $x.m(\cdots)$ is the result of applying m to x.

Examples

Let s be a variable whose type is `Sell`.

- `s.price` = the price in the object s.
- `s.bar.addr` = the address of the bar mentioned in s.
  - ❖ Note: cascade of dots OK because `s.bar` is an *object*, not a collection.

Example of Illegal Use of Dot

`b.beersSold.price`, where b is a `Bar` object.

- Why illegal? Because `b.beersSold` is a *set* of objects, not a single object.

OQL Select-From-Where

```
SELECT <list of values>
FROM <list of collections and
     typical members>
WHERE <condition>
```

- Collections in `FROM` can be:
  1. Extents.
  2. Expressions that evaluate to a collection.
- Following a collection is a name for a typical member, optionally preceded by `AS`.

Example

Get the menu at Joe's.

```
SELECT s.beer.name, s.price
FROM Sells s
WHERE s.bar.name = "Joe's Bar"
```

- Notice double-quoted strings in OQL.

Example

Another way to get Joe's menu, this time focusing on the `Bar` objects.

```
SELECT s.beer.name, s.price
FROM Bars b, b.beersSold s
WHERE b.name = "Joe's Bar"
```

- Notice that the typical object b in the first collection of `FROM` is used to help define the second collection.

Typical Usage

- If x is an object, you can extend the path expression, like s or `s.beer` in `s.beer.name`.
- If x is a collection, you use it in the `FROM` list, like `b.beersSold` above, if you want to access attributes of x.

Tailoring the Type of the Result

- Default: bag of structs, field names taken from the ends of path names in `SELECT` clause.

Example

```
SELECT s.beer.name, s.price
FROM Bars b, b.beersSold s
WHERE b.name = "Joe's Bar"
```

has result type:

```
Bag(Struct(
    name: string,
    price: real
))
```

Rename Fields

Prefix the path with the desired name and a colon.

Example

```
SELECT beer: s.beer.name, s.price
FROM Bars b, b.beersSold s
WHERE b.name = "Joe's Bar"
```

has type:

```
Bag(Struct(
    beer: string,
    price: real
))
```

Change the Collection Type

- Use `SELECT DISTINCT` to get a set of structs.

Example

```
SELECT DISTINCT s.beer.name, s.price
FROM Bars b, b.beersSold s
WHERE b.name = "Joe's Bar"
```

- Use `ORDER BY` clause to get a list of structs.

Example

```
joeMenu =
    SELECT s.beer.name, s.price
    FROM Bars b, b.beersSold s
    WHERE b.name = "Joe's Bar"
    ORDER BY s.price ASC
```

- `ASC` = ascending (default); `DESC` = descending.
- We can extract from a list as if it were an array, e.g.

```
cheapest = joeMenu[1].name;
```

Subqueries

- Used mainly in `FROM` clauses and with quantifiers `EXISTS` and `FORALL`.

Example: Subquery in `FROM`

Find the manufacturers of the beers served at Joe's.

```
SELECT DISTINCT b.manf
FROM (
        SELECT s.beer
        FROM Sells s
        WHERE s.bar.name = "Joe's Bar"
    ) b
```

Quantifiers

- Boolean-valued expressions for use in `WHERE`-clauses.

  `FOR ALL` x `IN` <collection> `:`
  <condition>

  `EXISTS` x `IN` <collection> `:`
  <condition>

- The expression has value `TRUE` if the condition is true for all (resp. at least one) elements of the collection.

Example

Find all bars that sell some beer for more than \$5.

```
SELECT b.name
FROM Bars b
WHERE EXISTS s IN b.beersSold :
    s.price > 5.00
```

Problem

How would you find the bars that *only* sold beers for more than \$5?

Example

Find the bars such that the only beers they sell for more than $5 are manufactured by Pete's.

```
SELECT b.name
FROM Bars b
WHERE FOR ALL be IN (
            SELECT s.beer
            FROM b.beersSold s
            WHERE s.price > 5.00
        ) :
    be.manf = "Pete's"
```